DIAGRAMMES

GILLES BERNOT

Good functors... are those preserving philosophy !

Diagrammes, tome 22 (1989), p. 15-29

[<http://www.numdam.org/item?id=DIA_1989__22__15_0>](http://www.numdam.org/item?id=DIA_1989__22__15_0)

© Université Paris 7, UER math., 1989, tous droits réservés.

L'accès aux archives de la revue « Diagrammes » implique l'accord avec les conditions générales d'utilisation (<http://www.numdam.org/conditions>). Toute utilisation commerciale ou impression systématique est constitutive d'une infraction pénale. Toute copie ou impression de ce fichier doit contenir la présente mention de copyright.

NUMDAM

Article numérisé dans le cadre du programme
Numérisation de documents anciens mathématiques
<http://www.numdam.org/>

GOOD FUNCTORS ... ARE THOSE PRESERVING PHILOSOPHY !

Gilles BERNOT

L.I.E.N.S.

U.R.A. C.N.R.S. 1327

Ecole Normale Supérieure

45 Rue d'Ulm

75230 Paris Cedex 05

FRANCE

Abstract :

Le but de cet article est de mettre en garde le chercheur en types abstraits algébriques contre une utilisation abusive de la théorie des catégories. Quelques propriétés peu souhaitables du (pourant classique) *foncteur de synthèse* sont décrites, spécialement si l'on s'intéresse aux sémantiques dites "loose". Tous les résultats énoncés ici sont particulièrement simples, sinon triviaux ; néanmoins, ils illustrent des faits donnant lieu à de nombreuses erreurs dans le cadre des types abstraits algébriques. Ces erreurs résultent souvent d'une inadéquation entre certains outils catégoriques bien connus et le concept informatique que l'on souhaite modéliser. Enfin, une approche hiérarchique fondée sur la catégorie des modèles "protégeant les sortes prédéfinies" est proposée, et les premières propriétés en sont dégagées.

Mots clés : complétude, consistance, modèle initial, spécifications abstraites, spécifications structurées, théorie des catégories, types abstraits algébriques.

1. Introduction

In the following pages, we focus our attention on results which seem to be "trivially ensured" in the basic abstract data type framework. We sometimes give proofs ... often counter-examples of such results. In order to get striking counter-examples, we provide very simple ones, if not trivial (mainly based on elementary algebraic properties of

Déjà paru dans les Proc. de "Category Theory and Computer Science", LNCS 283, 1987.

natural numbers). Nevertheless, many common errors, or misinterpretations found in the abstract data type literature result from similar mechanisms. This emphasizes the fact that category theory should be carefully used in the abstract data type field, including for (very) low level concepts.

More provocatively: this paper mainly points out the fact that the synthesis functor F of abstract data types “does not preserve philosophy.” However, since about ten years [ADJ 76], it is well known that this functor is crucial for defining a hierarchical, modular approach of abstract specifications!

Some elementary reminders about abstract data types are given in the next section (Section 2). Section 3 discusses about the well known *forgetful* and *synthesis functors*, U and F , associated with a hierarchical approach. Section 4 shows the difficulty of properly defining sufficient completeness and hierarchical consistency with loose semantics. In Section 5, we show what happens when combining enrichments. Lastly, Section 6 discusses about a loose semantics obtained by “protecting” predefined sorts.

The following discussions are mainly centered on pairs [positive fact / proof] (respectively: [negative fact / counter-example]).

2. Elementary reminders

Let us begin with basic definitions and properties [ADJ 76]:

Given a *signature* Σ (i.e. a finite set S of *sorts* and a finite set Σ of *operation-names* with arity in S), a Σ -algebra, A , is a heterogeneous set partitioned as $\{A_s\}_{s \in S}$, and for each operation-name $op: s_1 \cdots s_{n-1} \rightarrow s_n$ of Σ there is an operation $op_A: A_{s_1} \times \cdots \times A_{s_{n-1}} \rightarrow A_{s_n}$. A Σ -morphism from A to B is a sort-preserving, operation-preserving application from A to B . This defines a category, denoted by $\text{Alg}(\Sigma)$; it has an initial object: the ground-term algebra T_Σ .

In the following, a *specification* SPEC will be defined by a signature Σ and a finite set E of *positive conditional equations* of the form:

$$v_1 = w_1 \wedge \cdots \wedge v_{n-1} = w_{n-1} \Rightarrow v_n = w_n$$

where v_i and w_i are Σ -terms with variables.

Given a specification SPEC, $\text{Alg}(\text{SPEC})$ is the full sub-category of $\text{Alg}(\Sigma)$ whose objects are the Σ -algebras which validate each axiom of E . The category $\text{Alg}(\text{SPEC})$ has an initial object, denoted by T_{SPEC} [BPW 82].

Since T_{SPEC} exists, $\text{Gen}(\text{SPEC})$ can be defined as the full sub-category of $\text{Alg}(\text{SPEC})$ such that the initial morphism is an epimorphism (i.e. is *surjective*, in our framework). $\text{Gen}(\text{SPEC})$ is the category of the *finitely generated algebras*. Our first “fact” will be devoted to the following remark:

It is well known that $\text{Gen}(\text{SPEC})$ is a particularly interesting category for the abstract

data type computer scientist; nevertheless, this is not exactly due to its large spectrum of morphisms, as reminded below.

Fact 1 : *Morphisms from a finitely generated algebra*

Let Γ be an object of $\text{Gen}(\text{SPEC})$ and A an object of $\text{Alg}(\text{SPEC})$. The set $\text{Hom}_{\text{Alg}(\text{SPEC})}(\Gamma, A)$ contains *at most one element*. Consequently, for all objects X and Y of $\text{Gen}(\text{SPEC})$, $\text{Hom}_{\text{Gen}(\text{SPEC})}(X, Y)$ contains at most one morphism.

Proof :

By initiality properties, if there exists a morphism μ , then the following triangle commutes:

(For printing facilities, our triangles will become squares!)

$$\begin{array}{ccc}
 \Gamma & \xrightarrow{\quad - \mu \rightarrow \quad} & A \\
 \uparrow & & \uparrow \\
 \text{initial} & & \text{initial} \\
 \text{morphism} & & \text{morphism} \\
 | & & | \\
 T_{\text{SPEC}} & \xlongequal{\quad} & T_{\text{SPEC}}
 \end{array}$$

Thus, the unicity of μ results from the surjectivity of the initial morphism associated with Γ . $\square$

One of the most important aspect of abstract data types is its structured, hierarchical, modular approach. This is obtained by means of *presentations*. A presentation PRES over SPEC is a new “part of specification” $\text{PRES} = \langle S', \Sigma', E' \rangle$ such that the disjoint union $\text{SPEC} + \text{PRES} = \langle S \cup S', \Sigma \cup \Sigma', E \cup E' \rangle$ is a specification. Sorts and operations of SPEC are often called the *predefined* sorts and operations. Relations between the categories $\text{Alg}(\text{SPEC})$ and $\text{Alg}(\text{SPEC} + \text{PRES})$ are handled by the well known *forgetful functor* and *synthesis functor*:

$(U: \text{Alg}(\text{SPEC} + \text{PRES}) \rightarrow \text{Alg}(\text{SPEC}))$ and $(F: \text{Alg}(\text{SPEC}) \rightarrow \text{Alg}(\text{SPEC} + \text{PRES}))$.

The functor F is a left adjoint for the functor U . Consequently, for each SPEC -algebra A , there is a particular morphism from A to $U(F(A))$: the morphism deduced from the adjunction unit (or *adjunction morphism*). This morphism is absolutely crucial for the hierarchical approach: it allows to evaluate the modifications performed on A under the action of PRES .

Example 0 :

If A is equal to $\mathbb{N}$ over the signature $\{0, \text{succ}_-\}$ (without axioms) and if PRES adds pred_- with the axioms $[\text{pred}(\text{succ}(n)) = \text{succ}(\text{pred}(n)) = n]$, then $U(F(\mathbb{N}))$ is isomorphic to $\mathbb{Z}$. The unit of adjunction leads to the natural inclusion; and this morphism permits to show that $\mathbb{N}$ has been modified by adding negative values.

If the axioms were [$pred(succ(n))=n$ and $pred(0)=0$], then the unit of adjunction leads to the identity over N showing that this second specification of $pred$ does not change N .

3. Forgetful and synthesis functors

We first present a rather obvious reminder about the *forgetful functor*. Let B be a SPEC+PRES-algebra. The forgetful functor removes all subsets B_s where $s \in S'$, and all operations of Σ' are forgotten (including those with arity in S only), but *it does not remove any value of predefined sort*: $U(B_s)=B_s$ for each $s \in S$. For instance, in Example 0, $U(Z)=Z \neq N$.

Let us remind the classical definition of the *synthesis functor* (although classical, this definition is the starting point of some misinterpretations!): Let A be a SPEC-algebra and let $T_{\Sigma+\Sigma'(A)}$ be the algebra of $\Sigma+\Sigma'$ -terms with variables in A ; we denote by $eval: U(T_{\Sigma+\Sigma'(A)}) \rightarrow A$ the canonical evaluation morphism. $F(A)$ is the quotient of $T_{\Sigma+\Sigma'(A)}$ by the smallest congruence containing both the fibers of $eval$ and the close instantiations of $E+E'$.

Because $E+E'$ is required in the definition of F (instead of E' alone), $F(A)$ does not only depend on A and PRES ; it also depends on SPEC.

Fact 2 :

Given a presentation PRES, the action of the synthesis functor F over a given, fixed algebra A is highly dependent of the predefined specification.

As outlined in the following example, this fact considerably restricts the possibility of writing “implementation independent” specifications (see for instance [EKMP 80], [SW 82], or [BBC 86a] about abstract implementations).

Example 1 :

Let SPEC be a classical specification of NAT with operations 0 , $succ_$ and $_+_$:

$$\begin{aligned} x + 0 &= x \\ x + succ(y) &= succ(x+y) \end{aligned}$$

Let SPEC' be the specification obtained by adding the following axiom to SPEC :

$$x + y = x + z \quad \Rightarrow \quad y = z$$

The specifications SPEC and SPEC' have clearly the same initial object: N . In fact, they have the same finitely generated algebras because the previous axiom can be proved from SPEC via structural induction.

Let PRES be the presentation adding no sort, adding the operation $_ \times _$, and adding the axioms:

$$\begin{aligned}
x \times \text{succ}(0) &= x && (1 \text{ is neutral}) \\
x \times \text{succ}(y) &= x + (x \times y) && (\text{recursive definition})
\end{aligned}$$

When PRES is shown as a presentation over SPEC, $F(\mathbf{N})$ is a model where all terms containing a multiplication by 0 cannot be evaluated. When PRES is shown as a presentation over SPEC', $F(\mathbf{N})$ is isomorphic to $\mathbf{N}$, because:

$$x + 0 = x = x \times \text{succ}(0) = x + (x \times 0)$$

and the simplification axiom of SPEC' leads to $0 = x \times 0$.

Notice that, in spite of the fact that SPEC and SPEC' have the same finitely generated models and the same initial algebra, the presentation PRES is not completely specified over the first specification, but is completely specified over the second one.

4. Consistency and completeness

The subject of this section is an examination of some *a priori* possible definitions of the notions of *sufficient completeness* and *hierarchical consistency* with loose semantics. We start with the most loose semantics: the entire category $\text{Alg}(\text{SPEC})$. We will show that the simplest definitions are unacceptable for abstract specification purposes.

All the counter-examples provided in this section are based on the following specification+presentation example. Hopefully, we believe that this counter-example cannot be suspected to be too much unusual, complicated or *ad hoc*.

Example 2 :

Let SPEC be a specification of natural numbers (for instance the specification given in Example 1) together with a sort *BOOL* and boolean operations *True* and *False*. We consider the presentation PRES enriching SPEC by an equality predicate *eq?* :

$$\begin{aligned}
\text{eq?}(0,0) &= \text{True} \\
\text{eq?}(0,\text{succ}(n)) &= \text{False} \\
\text{eq?}(\text{succ}(m),0) &= \text{False} \\
\text{eq?}(\text{succ}(m),\text{succ}(n)) &= \text{eq?}(m,n)
\end{aligned}$$

Looking at this presentation PRES, we can affirm that a “good notion” of sufficient completeness (resp. hierarchical consistency) should be satisfied by PRES. This example is simply written by taking into account each possible value for the arguments of *eq?*, with respect to the constructors of SPEC, moreover there are no axioms between constructors (fair presentation [Bid 82]).

We may of course imagine more sophisticated presentation examples, in particular examples which add new sorts to SPEC. But our goal is simply to prevent the abstract data type researcher from using a naive, rather unrealistic definition of sufficient

completeness or hierarchical consistency.

4.1. Sufficient completeness

In the initial approach, sufficient completeness is defined as follows [Gau 78].

“The adjunction morphism associated with the initial algebra is surjective.”

$$T_{\text{SPEC}} \rightarrow U(F(T_{\text{SPEC}}))$$

This condition exactly means that PRES does not add new values to T_{SPEC} . Remind that $F(T_{\text{SPEC}}) = T_{\text{SPEC}+\text{PRES}}$, due to adjunction properties.

Fact 3 :

The following definition of sufficient completeness is not suitable in the general case:

“PRES is sufficiently complete if and only if for all algebras in $\text{Alg}(\text{SPEC})$ the adjunction morphism is surjective”.

Using Example 2, we convince ourselves of this fact by considering the SPEC-algebra obtained by two copies of N. This algebra, $(N \times \{0,1\} \text{ and } \{True, False\})$, is not finitely generated, but is an object of $\text{Alg}(\text{SPEC})$ by sending the operation-name 0 over the element $(0,0)$, and $\text{succ}((n,a)) = (\text{succ}(n), a)$. Terms of the form $\text{eq}((n,0), (m,1))$ cannot be evaluated using the PRES axioms of Example 2. Consequently, they add new boolean values, and the adjunction morphism is not surjective.

Fact 4 :

The following two definitions of sufficient completeness are logically equivalent:

- 1) *the adjunction morphism associated with the initial algebra T_{SPEC} is surjective*
- 2) *for all algebras in $\text{Gen}(\text{SPEC})$ the adjunction morphism is surjective.*

Proof :

$[2 \Rightarrow 1]$ is trivial because the initial algebra is finitely generated.

$[1 \Rightarrow 2]$: let A be a finitely generated SPEC-algebra. By construction of F , $F(A)$ is finitely generated over the signature of $\text{SPEC}+\text{PRES}$. Consequently, the image of the initial morphism via the forgetful functor is surjective:

$$U(\text{init}_A): U(F(T_{\text{SPEC}})) = U(T_{\text{SPEC}+\text{PRES}}) \rightarrow U(F(A))$$

Our conclusion results from the commutativity of the following diagram:

$$\begin{array}{ccc}
A & \xrightarrow{\text{--adjunction--}} & U(F(A)) \\
\uparrow & & \uparrow \\
\text{surjective} & & \text{surjective} \\
| & & | \\
T_{\text{SPEC}} & \xrightarrow{\text{--surjective--}} & U(T_{\text{SPEC}+\text{PRES}})
\end{array}$$

Restricting ourselves to finitely generated algebras has several disadvantages. For instance, parameterized presentations require a non finitely generated semantics [ADJ 80].

4.2. Hierarchical consistency

In the initial approach, hierarchical consistency is defined as follows:

“the adjunction morphism associated with the initial algebra is a monomorphism”
(i.e. is *injective* in our framework).

Fact 5 :

The following definition of hierarchical consistency is not suitable in the general case:

“PRES is hierarchically consistent if and only if for all algebras in Alg(SPEC) the adjunction morphism is injective”.

Let us return to Example 2. If we consider the SPEC-algebra $\mathbf{Z}$ (which is a non finitely generated algebra), we get the following inconsistency:

$$\text{True} = \text{eq?}(0,0) = \text{eq?}(0,\text{succ}(-1)) = \text{False}$$

Restricting hierarchical consistency checks to finitely generated algebras does not yield better results:

Fact 6 :

The following definition of hierarchical consistency is not suitable in the general case:

“PRES is hierarchically consistent if and only if for all algebras in Gen(SPEC) the adjunction morphism is injective”.

Using Example 2 again, we consider a finitely generated algebra of the form $\frac{\mathbf{Z}}{n\mathbf{Z}}$, and we get the following inconsistency:

$$\text{True} = \text{eq?}(0,0) = \text{eq?}(0,n) = \text{eq?}(0,\text{succ}(n-1)) = \text{False}$$

These facts prove that “defining sufficient completeness on $\text{Alg}(\text{SPEC})$ ”, “defining hierarchical consistency on $\text{Alg}(\text{SPEC})$ ” or “defining hierarchical consistency on $\text{Gen}(\text{SPEC})$ ” are too strong requirements. Extension from the purely initial semantics to a loose semantics must be done more carefully.

5. Combining presentations

In the remainder of this paper, we simply follow the definitions of sufficient completeness and hierarchical consistency given at the beginning of sections 4.1 and 4.2 (i.e. the initial approach). Given a specification SPEC , we consider two presentations PRES_1 and PRES_2 with disjoint signatures.

Let PRES be the union of PRES_1 and PRES_2 , we care about the sufficient completeness and hierarchical consistency of PRES . In spite of the strong hypothesis described here, we have sometimes to be careful, as detailed in the following two subsections.

5.1. Sufficient completeness

Fact 7 :

If PRES_1 and PRES_2 are both sufficiently complete over SPEC , then $\text{PRES} = \text{PRES}_1 + \text{PRES}_2$ remain sufficiently complete. Moreover, under the same hypothesis, PRES_2 is sufficiently complete over $\text{SPEC} + \text{PRES}_1$.

Proof : (using elementary tools)

$T_{\text{SPEC} + \text{PRES}_1 + \text{PRES}_2}$ is the quotient of $T_{\Sigma + \Sigma_1 + \Sigma_2}$ by the smallest congruence containing the close instantiations of the $\text{SPEC} + \text{PRES}_1 + \text{PRES}_2$ axioms [BPW 82]. Consequently, it suffices to prove that each $\Sigma + \Sigma_1 + \Sigma_2$ -ground-term of sort in S (resp. in $S + S_1$) belongs to the equivalence class of a Σ -term (resp. $\Sigma + \Sigma_1$ -term). This can be trivially proved via structural induction. $\square$

Obviously, the converse is false: the sufficient completeness of PRES does not imply the sufficient completeness of PRES_1 or PRES_2 .

5.2. Hierarchical consistency

Fact 8 :

The hierarchical consistency of PRES_1 and PRES_2 over SPEC does not imply the hierarchical consistency of $\text{PRES} = \text{PRES}_1 + \text{PRES}_2$ over SPEC .

Example 3 :

Let SPEC be a specification of natural numbers. Let PRES_1 be the presentation

simply containing the following axiom:

$$\text{succ}(n) = 0 \quad \Rightarrow \quad n = 0$$

PRES_1 is clearly consistent (in fact, the premise cannot be satisfied in the initial object, thus this axiom is never applied). Let PRES_2 be the presentation adding the operation pred_- with $[\text{pred}(\text{succ}(n)) = \text{succ}(\text{pred}(n)) = n]$. PRES_2 is clearly hierarchically consistent over natural numbers (even though it is not sufficiently complete). The union $\text{PRES} = \text{PRES}_1 + \text{PRES}_2$ is not hierarchically consistent because from $\text{succ}(\text{pred}(0)) = 0$ we get:

$$0 = \text{pred}(0), \quad \text{which leads to} \quad \text{succ}(0) = \text{succ}(\text{pred}(0)) = 0$$

Another example of the same fact is the following:

Example 4 :

Let PRES_1 be the presentation described in Example 2 (adding equality predicate to natural numbers), and let PRES_2 be the same presentation as Example 3 before (adding pred). PRES_1 and PRES_2 are clearly hierarchically consistent over natural numbers, but the union $\text{PRES} = \text{PRES}_1 + \text{PRES}_2$ is not hierarchically consistent because:

$$\text{True} = \text{eq?}(0,0) = \text{eq?}(0, \text{succ}(\text{pred}(0))) = \text{False}$$

(a similar example was first presented in [EKP 80], for abstract implementation purposes).

Fact 9 :

If $\text{PRES} = \text{PRES}_1 + \text{PRES}_2$ is hierarchically consistent over SPEC , then PRES_1 and PRES_2 are hierarchically consistent over SPEC .

Proof :

Assume that PRES_1 is not consistent: the morphism from T_{SPEC} to $U(T_{\text{SPEC} + \text{PRES}_1})$ is not injective. Since the following diagram commutes, the adjunction morphism from T_{SPEC} to $T_{\text{SPEC} + \text{PRES}_1 + \text{PRES}_2}$ is not injective:

$$\begin{array}{ccc} U_1(T_{\text{SPEC} + \text{PRES}_1}) & \rightarrow & U(T_{\text{SPEC} + \text{PRES}_1 + \text{PRES}_2}) \\ \uparrow & & \uparrow \\ \text{PRES}_1 & & \text{PRES}_1 + \text{PRES}_2 \\ \text{adjunction morphism} & & \text{adjunction morphism} \\ | & & | \\ T_{\text{SPEC}} & \xlongequal{\quad} & T_{\text{SPEC}} \end{array}$$

$\text{SPEC} + \text{PRES}_1$).

It results that PRES is not hierarchically consistent over SPEC . $\square$

Fact 10 :

If $PRES_1$ and $PRES_2$ are both hierarchically consistent and sufficiently complete over $SPEC$, then $PRES = PRES_1 + PRES_2$ too. Moreover, under the same hypothesis, $PRES_2$ is hierarchically consistent and sufficiently complete over $SPEC + PRES_1$.

(This fact is well known; a demonstration with conditional axioms, including exception handling, can be found in [Ber 86]).

6. Loose semantics with “Protect”

Clearly, abstract specifications do not necessarily directly lead to executable specifications. It is often convenient to specify some operations via “universal properties.” For instance the subtraction can be specified via:

$$z - y = x \quad \Longleftrightarrow \quad x + y = z$$

Sometimes, such axioms may lead to uncompletely specified presentations, as in the following example.

Example 5 :

Let $SPEC$ be an initial specification of integers with operations 0 , $succ_$, $pred_$, $_+ _$, $_- _$ and $_ \times _$. Let us specify a presentation $PRES$ adding the operation $_div _$ as follows:

$$\begin{aligned} 0 \leq (a - (b \times (a \div b))) &= True \\ (a - (b \times (a \div b))) < b &= True \end{aligned}$$

These axioms characterize $(a \div b)$ among all integers *finitely generated* with respect to $succ$ and $pred$. However, in the initial model $T_{SPEC+PRES}$, the term $(a \div b)$ is not reached by $succ$ and $pred$. Its value is only a unreachable value such that the (unreachable) remainder $(a - (b \times (a \div b)))$ returns the specified boolean values when compared with 0 and b .

Consequently, this presentation is uncompletely specified according to the usual definition of sufficient completeness.

In such examples, the only interesting models are those which do not modify the predefined initial model (Z) . This leads to a (loose) semantics where models are those *protecting* predefined sorts [Kam 80]. Indeed, when writing relatively large specifications, this semantics seems to be highly suitable (ASL [Wir 82] [SW 83], PLUSS [Gau 84], OBJ [FGJM 85], LARCH [GH 83] ...).

Let us define the associated category:

Definition : *The “Protect” category*

Let SPEC be a specification and let PRES be a presentation over SPEC. The category of PRES-models protecting SPEC is the full subcategory of $\text{Alg}(\text{SPEC}+\text{PRES})$ whose objects are the SPEC+PRES-algebras A such that $U(A)$ is isomorphic to the initial predefined algebra T_{SPEC} . We denote this category by $\text{Pro}(\text{SPEC},\text{PRES})$.

Notice that the object class of $\text{Pro}(\text{SPEC},\text{PRES})$ can be empty.

Fact 11 :

If $\text{Pro}(\text{SPEC},\text{PRES})$ is not an empty category, then PRES is hierarchically consistent over SPEC.

(Here, consistency is defined with respect to the initial algebra T_{SPEC} only)

Proof :

If $T_{\text{SPEC}+\text{PRES}}$ is inconsistent over T_{SPEC} , then a fortiori all SPEC+PRES-algebras are inconsistent over T_{SPEC} (because $T_{\text{SPEC}+\text{PRES}}$ is minimal). $\square$

Fact 12 :

Even if PRES is consistent over SPEC, $\text{Pro}(\text{SPEC},\text{PRES})$ may be empty.

Example 6 :

Let SPEC be the boolean specification with *True* and *False*. Let PRES be a specification of $\text{SET}(\text{BOOL})$ with $\emptyset$, *insert*, $\in$ and *choose* :

$$\begin{aligned} \text{True} \in \emptyset &= \text{False} \\ \text{False} \in \emptyset &= \text{False} \\ b \in \text{insert}(b', X) &= b=b' \text{ or } b \in X \\ \text{choose}(X) \in X &= \text{True} \end{aligned}$$

This specification is clearly hierarchically consistent (even though it is not sufficiently complete). However, the Protect category is empty, because the term $\text{choose}(\emptyset)$ can neither be equal to *True* nor to *False* (both choices induce $\text{True}=\text{False}$).

(Fortunately, this example can be easily specified without inconsistency using abstract data types with exception handling [Bid 84] [GDLE 84] [BBC 86b] [Ber 86], or with partial functions [BW 82].)

Fact 13 :

Even if $\text{Pro}(\text{SPEC},\text{PRES})$ contains models, it has not necessarily an initial object.

Example 7 :

Let SPEC be the boolean specification with *True* and *False*. Let PRES be the presentation adding the constant operation *maybe*, without any axiom. $\text{Pro}(\text{SPEC}, \text{PRES})$ contains two models, no one is initial.

Fact 14 :

If PRES is sufficiently complete over SPEC, then either $\text{Pro}(\text{SPEC}, \text{PRES})$ has an initial object, either it is empty.

Proof :

If PRES is consistent, then the initial model $T_{\text{SPEC}+\text{PRES}}$ belongs to $\text{Pro}(\text{SPEC}, \text{PRES})$; it is then necessarily initial in $\text{Pro}(\text{SPEC}, \text{PRES})$. If PRES is not hierarchically consistent, then Fact 11 implies that $\text{Pro}(\text{SPEC}, \text{PRES})$ has no object. $\square$

Fact 15 :

There are presentations PRES which are not sufficiently complete over SPEC, such that $\text{Pro}(\text{SPEC}, \text{PRES})$ is not empty and has an initial object.

It suffices to refer to Example 5, where the axioms characterize *div* by a “universal property among integers.” The division is incompletely specified according to classical initial definition of sufficient completeness, but $\text{Pro}(\text{SPEC}, \text{PRES})$ only contains one model (**Z**) which is necessarily initial.

7. Conclusion

We have investigated how a hierarchical approach of abstract data types, with the notions of *hierarchical consistency* and *sufficient completeness*, could be defined when dealing with so-called *loose semantics*. The results shown in sections 2 to 5 seem to be somewhat pessimistic:

- The synthesis functor is “implementation dependent” with respect to the predefined specification (Fact 2).
- Sufficient completeness cannot be checked on all models (Fact 3).
- Hierarchical consistency cannot be checked on all models (Fact 5).
- Hierarchical consistency cannot be checked on all finitely generated models, a smaller class of models must be investigated (Fact 6).
- Combining hierarchically consistent presentations does not result on a hierarchically consistent presentation (Fact 8).

However, we showed some positive results:

- Checking sufficient completeness on all finitely generated algebras is equivalent to check it on the initial algebra only (Fact 4).
- Combining sufficiently complete presentations results on sufficiently complete presentations (Fact 7); the same occurs for presentations that are both sufficiently complete and hierarchically consistent (Fact 10).

In the last section (Section 6), we defined the category of models *protecting predefined sorts*. We have investigated the relations between the classical notions of completeness/consistency and the elementary properties of this category:

- The category is empty if the presentation is not hierarchically consistent, but the converse is false (Facts 11 & 12).
- The category has not necessarily initial models (Fact 13).
It has initial models if the presentation is sufficiently complete and hierarchically consistent, but the converse is false (Facts 14 & 15).

In conclusion: From facts 2, 3, 5, 6 and 8, we showed that the synthesis functor of classical abstract data types “does not always preserve philosophy” when dealing with loose semantics. Moreover, with a loose semantics based on protection of predefined sorts, the corresponding category has few systematic relations with sufficient completeness or hierarchical consistency (facts 11 to 15).

Acknowledgements :

It is a pleasure to express gratitude to Michel Bidoit, Christine Choppy and Marie-Claude Gaudel for encouragements to write this paper and careful proof readings. The title was suggested by Stephane Kaplan.

8. References

- [ADJ 76] Goguen J., Thatcher J., Wagner E. : *"An initial algebra approach to the specification, correctness, and implementation of abstract data types"*, Current Trends in Programming Methodology, Vol.4, Yeh Ed. Prentice Hall, 1978. Also : IBM Report RC 6487, Oct. 1976.
- [ADJ 80] Ehrig H., Kreowski H., Thatcher J., Wagner J., Wright J. : *"Parameterized data types in algebraic specification languages"*, Proc. 7th ICALP, July 1980.
- [BBC 86.a] Bernot G., Bidoit M., Choppy C. : *"Abstract implementations and correctness proofs"*, Proc. 3rd STACS, January 1986, Springer-Verlag LNCS 210, January 1986. Also : LRI Report 250, Orsay, Dec. 1985.
- [BBC 86b] G. Bernot, M. Bidoit, C. Choppy : *"Abstract data types with exception handling : an initial approach based on a distinction between exceptions and errors"*, Theoretical Computer Science, Vol. 46, n° 1, p. 13-45, November 1986.
- [Ber 86] Bernot G. : *"Une sémantique algébrique pour une spécification différenciée des exceptions et des erreurs : application à l'implémentation et aux primitives de structuration des spécifications formelles"*, Thèse de troisième cycle, LRI, Université de Paris-Sud, Orsay, Février 1986.
- [Bid 82] Bidoit M. : *"Algebraic data types: structured specifications and fair presentations"*, Proc. AFCET Symposium on Mathematics for Computer Science, Paris, March 1982.
- [Bid 84] Bidoit M. : *"Algebraic specification of exception handling by means of declarations and equations"*, Proc. 11th ICALP, Springer-Verlag LNCS 172, July 1984.
- [BPW 82] Broy M., Pair C., Wirsing M. : *"A systematic study of models of abstract data types"*, Theoretical Computer Sciences, p. 139-174, vol. 33, October 1984.
- [BW 82] Broy M., Wirsing M. : *"Partial abstract data types"*, Acta Informatica, Vol.18-1, Nov. 1982.
- [EKMP 80] Ehrig H., Kreowski H., Mahr B., Padawitz P. : *"Algebraic implementation of abstract data types"*, Theoretical Computer Science, Oct. 1980.
- [EKP 80] Ehrig H., Kreowski H., Padawitz P. : *"Algebraic implementation of abstract data types: concept, syntax, semantics and correctness"*, Proc. ICALP, Springer-Verlag LNCS 85, 1980.

- [FGJM 85] Futatsugi K., Goguen J., Jouannaud J-P., Meseguer J. : "*Principles of OBJ2*", Proc. 12th ACM Symp. on Principle of Programming Languages, New Orleans, January 1985.
- [Gau 78] Gaudel M-C. : "*Spécifications incomplètes mais suffisantes de la représentation des types abstraits*", Laboria Report 320, 1978.
- [Gau 84] Gaudel M-C. : "*A first introduction to PLUSS*", LRI Report, Orsay, December 1984.
- [GDLE 84] Gogolla M., Drosten K., Lipeck U., Ehrich H.D. : "*Algebraic and operational semantics of specifications allowing exceptions and errors*", Theoretical Computer Science 34, North Holland, 1984.
- [GH 83] Guttag J.V., Horning J.J. : "*An introduction to the LARCH shared language*", Proc. IFIP 83, REA Mason ed., North Holland Publishing Company, 1983.
- [Kam 80] Kamin S. : "*Final data type specifications : a new data type specification method*", Proc. of the 7th POPL Conference, 1980.
- [SW 82] Sannella D., Wirsing M. : "*Implementation of parameterized specifications*", Report CSR-103-82, Department of Computer Science, University of Edinburgh.
- [SW 83] Sannella D., Wirsing M. : "*A kernel language for algebraic specification and implementation*", Proc. Intl. Conf. on Foundations of computation Theory, Springer-Verlag, LNCS 158, 1983.
- [Wir 82] Wirsing M. : "*Structured algebraic specifications*", Proc. of AFCET Symposium on Mathematics for Computer Science, Paris, March 1982.